



NOTES:

1. CONCRETE SHALL BE NORMAL-CLASS N25 STANDARD STRENGTH GRADE COMPLYING WITH THE REQUIREMENT OF AS 1379. REFER TO VICROADS STANDARD SPECIFICATIONS SECTION 703 FOR REQUIREMENTS OF CONCRETE TO BE USED IN KERBS EXTRUSION MACHINES
2. REFER TO ROAD DESIGN GUIDELINES PART 3 FOR THE RECOMMENDED USE TO KERB AND CHANNELS
3. MOUNTABLE KERBS M4,M5 AND M6 ARE DESIGNED TO DISCOURAGE MOST TRAFFIC FROM MOUNTING A TRAFFIC ISLAND OR MEDIAN EXCEPT FOR LONG OR OVER DIMENSIONAL VEHICLES.EG. THE KERBS ON THE OUTER EDGE OF THE MOUNTABLE APRON OF A ROUNDABOUT'S CENTRAL ISLAND. THESE KERBS SHALL NOT BE USED WHERE THERE IS A LIKELIHOOD THAT CYCLISTS , PEDESTRIANS OR PRAMS WILL HAVE TO CROSS THE KERB.



KERB PROFILES 1
(Not To Scale)

DRAWN BY:
C.B.
CHECKED : L.T
DATE:
05.04.13
SD 009

REVISION	DATE	APPROVED
1.	27.8.2009	J.G.
2.	5.04.2013	L.T.
3.		